

POOL & SPA PRODUCT PORTFOLIO



Residential



Apartment
Buildings



Schools, Colleges,
& Universities



Hotels
& Restaurants



Non-Profit
Organizations



Pool & Spa

RESIDENTIAL POOL & SPA HEATERS



AVIA®

264 MBTUH - 399 MBTUH
84% Efficiency

Featuring ProTek Shield™,
Raymote® connectivity, Low
NO_x design.



AVIA® with NiTek

264 MBTUH - 399 MBTUH
84% Efficiency

Featuring ProTek Shield™,
Raymote® connectivity, Low
NO_x design, NiTek™ Heat
Exchanger Technology.



Digital

199 MBTUH - 399 MBTUH
82% Efficiency

Featuring ProTek Shield™,
also available as Millivolt,
Cupronickel.



Above Ground

105 MBTUH & 150 MBTUH
82% Efficiency

Analog (106 Model) or Digital
Control (156 Model).



Crosswind®

28 MBTUH - 61 MBTUH
5.8 ~ 5.7 C.O.P. (80,80,80)¹

27 MBTUH - 58 MBTUH
5.6 ~ 5.3 C.O.P. (80,63,80)¹



Crosswind® V

85 MBTUH - 138 MBTUH
5.8 ~ 6.0 C.O.P. (80,80,80)¹

80 MBTUH - 130 MBTUH
5.5 ~ 5.8 C.O.P. (80,63,80)¹



Classic & Compact Series

48 MBTUH - 140 MBTUH
5.7 ~ 5.6 C.O.P. (80,80,80)¹

46 MBTUH - 130 MBTUH
5.5 ~ 5.3 C.O.P. (80,63,80)¹



E3T®

19 MBTUH - 92 MBTUH
5.5 - 27 kW

 Raymote Equipped

 Gas  Electric  Heat Pump

PROFESSIONAL POOL & SPA HEATERS



Digital ASME 🔥

199 MBTUH - 399 MBTUH
82% Efficiency

*Featuring ProTek Shield™,
also available as Low NO_x,
Cupronickel.*



Professional 🔥

266 MBTUH - 399 MBTUH

Featuring ProTek Shield™.



Professional X94 🔥

399 MBTUH
94% Efficiency



Professional Heat Pump 🌬️

140 MBTUH - 170 MBTUH
6.1 ~ 5.8 C.O.P. (80,80,80)1

133 MBTUH - 155 MBTUH
5.8 ~ 5.3 C.O.P. (80,63,80)1



PROFESSIONAL POOL & SPA HEATERS



XTherm® Indirect 🔥 🔌

1 MMBTUH - 2 MMBTUH
Up to 96% Efficiency

Cupronickel indirect heat exchanger standard. Titanium indirect heat exchanger and warranty upgrade option. Cascades up to 8 units.



XTherm® 🔥 🔌

1 MMBTUH - 4 MMBTUH
97% Efficiency

Hybrid: cupronickel finned water-tube heat exchanger with secondary stainless steel condensing water-tube heat exchanger. Cascades up to 8 units.



MVB® 🔥 🔌

500 MBTUH - 2 MMBTUH
83-83.3% Efficiency

Cascades up to 8 units.



Hi Delta® 🔥

500 MBTUH - 2.3 MMBTUH
83.1% Efficiency

Cascades up to 8 units. SureRack® vertical racking option.



E3T® 3-Phase ⚡

61 MMBTUH - 184 MMBTUH
18 - 54kW

80-character display. Durable against salt pool water conditions, standard on all models. Includes Flow Protection, Low-Temp Operating Mode, Load Detection, and 50/50 Mode².



Scan here to visit the Raypak Pool Products page

Residential | Professional | Protégé

🔌 Raymote Equipped

🔥 Gas ⚡ Electric 🔌 Heat Pump

¹ Tested to AHRI 1160

² Available on models with 6 heating elements.