



PoolSync
READY!



DEPENDABILITY and
EFFICIENCY for
pool heating

Control from a
CONVENIENT
phone app



TropiCal[®]

GET THE MOST OUT OF YOUR POOL HEATING INVESTMENT!

- High performance titanium heat exchanger maximizes flow efficiency (Patented ThermoLink® in T90, T115 and T135)
- Weather protected microprocessor control with water temperature setpoint dial (60°-104° F), easy to use and compatible with most external controllers
- Impact resistant, rust and fade proof cabinet with built-in drain pan provides condensate management
- Quieter than conventional heat pumps



Now PoolSync® Ready

- Adjust your temperature setting right through your phone in the PoolSync app

*Additional purchase of PoolSync WiFi Controller required

| | | T55 | T75 | T90 | T115 | T135 |
|---|--|-----------------|-----------------|-----------------|-----------------|-----------------|
| BTUs (water temp/ambient air/ relative humidity) | 80/80/80 | 52,000 | 74,000 | 96,000 | 112,000 | 132,000 |
| | 80/80/63 | 50,000 | 70,000 | 90,000 | 106,000 | 125,000 |
| | 80/50/63 | 33,000 | 49,000 | 65,000 | 74,000 | 84,000 |
| C.O.P. Coefficient of Performance (water temp/ambient air/ relative humidity) | 80/80/80 | 6.0 | 5.6 | 6.0 | 5.6 | 5.7 |
| | 80/80/63 | 5.8 | 5.4 | 5.8 | 5.4 | 5.6 |
| | 80/50/63 | 4.0 | 4.0 | 4.2 | 4.0 | 4.0 |
| Refrigerant | | R410A | R410A | R410A | R410A | R410A |
| Heat Exchanger | | Tube in Tube | Tube in Tube | ThermoLink® | ThermoLink® | ThermoLink® |
| Electrical | kW Input | 2.7 | 3.9 | 4.7 | 5.9 | 6.8 |
| | Voltage/Hz/Phase | 208-230/60/1 | 208-230/60/1 | 208-230/60/1 | 208-230/60/1 | 208-230/60/1 |
| | Min. Circuit Ampacity | 22.6 | 31.4 | 40.2 | 38.2 | 43.3 |
| | Max. Fuse Size | 30 | 50 | 60 | 60 | 60 |
| Water Flow | Min./Max. (gpm) | 20/45 | 20/45 | 30/70 | 30/70 | 30/70 |
| | A Heater Bypass Kit is required when flow rates exceed the maximum: part number STK0135. | | | | | |
| Physical | Weight (lbs) | 196 | 208 | 231 | 261 | 262 |
| | Length x Width x Height (in) | 34" x 34" x 28" | 34" x 34" x 28" | 34" x 34" x 39" | 34" x 34" x 39" | 34" x 34" x 39" |
| Shipping | Weight (lbs) | 236 | 248 | 271 | 301 | 302 |
| | Length x Width x Height (in) | 37" x 36" x 34" | 37" x 36" x 34" | 37" x 36" x 45" | 37" x 36" x 45" | 37" x 36" x 45" |

Rated in accordance with AHRI standard 1160 water temp/ambient air/relative humidity
Specifications subject to change



A portion of every heat pump sold will be donated to Every Child a Swimmer



WWW.
AQUACAL
.COM



California residents visit aquacal.com
for Proposition 65 information.



AC-1821.2_23 V9